

MICAPS SVS3CMOS2800CA

C-mount USB3.0 CMOS Cameras SONY PREGIUS CMOS Sensor



SVS3CMOS2800CA is USB3.0 interface color Camera for industrial applications, having built-in hardware ISP to ensure color reproduction and higher video speed. The camera resolution coverage is 2.8MP.

Features

- Sony PREGIUS CMOS sensor
- Two-step noise reduction technology
- Ultra-high sensitivity and low noise
- USB 3.0 data transmission interface compatible with USB2.0 protocol
- Provides advanced video and image processing application software MicroView
- Supports external triggering, digital I/O and free-running modes
- Supports ROI, flip, bit-depth switching and other features

Applications

- Scientific research, education (teaching, demonstration and academic exchanges)
- Digital laboratory, medical research
- Industrial visual (PCB examination, IC quality control)
- Medical treatment (pathological observation)
- Food (microbial colony observation and counting)
- Aerospace, military (high sophisticated weapons)

Model No.	Sensor & Size(mm)	Pixel(μm)	G Sensitivity Dark Signal	FPS/Resolution	Binning	Exposure
SVS3 with 38mmx38mmx33mm housing						
SVS3CMOS2800CA	2.8M/IMX421LQJ(C,GS) 2/3" (8.71x6.59)	4.5x4.5	2058mv with 1/30s 0.15mv with 1/30s	121fps@1936x1464 425fps@968x732	1x1 1x1	6us~15s 38mm


C: Color, GS: Global Shutter

General Specification

Power supply	Power with USB3.0
Power consumption	<3.0W
Temperature	Working temperature -10~50°C, storage temperature 30~70°C
Platform and architecture	Win32/WinRT/Linux/macOS/Android; X86/X64/armhf/armel/arm64
Size	33mmx33mmx33mm, 38mmx38mmx33mm
Weight	227g
Lens mount	C-mount
Humidity	20%-80%, no condensation
Certification	CE, FCC

Camera Interface

Check out the back of the industrial camera in the figure. It features a standard USB 3.0 output, a 7-pin I/O port with an aviation head, and an on/off indicator. There are also two M2 screw holes on either side of the USB 3.0 port to secure the cable, helping to prevent it from loosening due to vibrations in the field.



LABLINK INSTRUMENTS

- Plot no. 435, Sector 2, HSIIDC Saha, Saha, Ambala (Haryana) India - 133104.
- Plot no 3-6-164/2, 2nd Street, Hyderguda Himayatnagar, Hyderabad (Telangana) India - 500029

Contact us:

Email:- info@lablinkinstruments.com
www.lablinkinstruments.com, www.micaps.com